



|  |            |                         |            |               |
|--|------------|-------------------------|------------|---------------|
| 4/3" 2.0/16mm C                                |            | 4/3"                    | 1"         | 2/3"          |
| FOCAL LENGTH                                   |            | f=16mm                  |            |               |
| MAX. DIAMETER (RATIO)                          |            | F=1:2.0~22              |            |               |
| ELEMENT  |            | 9 GROUPS 11 ELEMENTS    |            |               |
| PICTURE SIZE                                   |            | 13.8x18.4mm             | 9.6x12.8mm | 6.6x8.8mm     |
| ANGLE  | VER. ANGLE | 47.2°                   | 33.6°      | 23.3°         |
|  | HOR. ANGLE | 60.6°                   | 44.0°      | 30.9°         |
|  | DIA. ANGLE | 72.0°                   | 53.7°      | 38.2°         |
| DISTORTION (TV)                                |            | 0.02%                   |            |               |
| SHOOTING RANGE AT<br>MINIMUM FOCUS<br>DISTANCE | VER.       | 100.8mm                 | 69.9mm     | 48.0mm        |
|  | HOR.       | 134.6mm                 | 93.5mm     | 64.0mm        |
|  | DIA.       | 167.6mm                 | 117.1mm    | 80.2mm        |
| MINIMUM FOCUS DISTANCE                         |            | 0.1m                    |            |               |
| FLANGE BACK                                    |            | 17.526mm in air         |            |               |
| BACK FOCUS                                     |            | 13.0mm in air           |            |               |
| FILTER SCREW SIZE                              |            | M40.5x0.5               |            |               |
| FRONT/REAR EFFECTIVE DIA.                      |            | FRONT φ31.2mm           |            | REAR φ16.5mm  |
| MOUNT  |            | C-MOUNT                 |            |               |
| EXIT PUPIL                                     |            | -38.0mm                 |            |               |
| TEMPERATURE RANGE                              |            | -10~+50°C               |            |               |
| STORAGE TEMPERATURE RANGE                      |            | -20~+60°C               |            |               |
| RESOLUTION CENTER/CORNER                       |            | CENTER 160本/mm          |            | CORNER 80本/mm |
| LENS COATING                                   |            | WIDE BAND MULTI COATING |            |               |
| WEIGHT   |            | 250 g                   |            |               |

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。



|            |               |     |                  |      |           |
|------------|---------------|-----|------------------|------|-----------|
|            |               | 尺度  | 1/1              | 工場番号 | FR1047KWN |
|            |               | 機種名 | 4/3" F2.0 f=16mm |      |           |
| 2019.7.8   | 絞り指標訂正(「8」削除) | 機種番 | LM16XC 外観図       |      |           |
| 2014.12.25 | 更新            |     |                  |      |           |
| 2013.4.15  | 作成年月日         |     |                  |      |           |