



2/3" 1.6/25mm C		1/2"	1/3"
Focal Length		f=25mm±5%	
Max. Diameter (Ratio)		F=1 : 1.6±5%	
Element		5 Group 5 Elements	
Picture Size		6.6x8.8mm	3.6x4.8
Angle	Ver.	15.7°	8.6°
	Hor.	21.0°	11.5°
	Dia.	26.3°	14.3°
Distortion(TV)		-0.6%	-0.1%
Shooting Range at M. O. D.	Ver.	275mm	149.1mm
	Hor.	368mm	199.0mm
	Dia.	465mm	249.2mm
Minimum Object Distance		1.0m	
Flange Back		17.526 +0.13 -0 mm in air	
Back Focus		10.32mm in air	
Filter Screw Size		M30.5x0.5	
Front/Rear Effective Dia.		F: φ 14.6mm	R: φ 10.7mm
Mount		C-MOUNT	
Exit Pupil		-26.2mm	
Temperature Range		-10~+45° C	
Storage Temperature Range		-40~+60° C	
Resolution		Center: 100 LP/mm	Corner: 40LP/mm
Stopper Strength		10kgf · cm	
Endurance Tests		Iris: 5,000Times	Focus: 5,000Times
Operating Torque		Iris: 50~600gf · cm	Focus: 100~1000gf · cm
Weight		42g±5g	

LM25JCR